



Accoat Standard Guide Wire – Lunderquist PTC



Dimensions

Ø 0.025" / 0.64 mm
Ø 0.035" / 0.89 mm

Length

50 cm
60 cm
70 cm
80 cm
90 cm
100 cm
120 cm
150 cm
260 cm

Surface

Stainless steel
PTFE coated

Distal tip form

Straight tip
J-tip radius: 1,5 – 3 – 6 – 15 mm

Distal flexible length

5 cm
7 cm
10 cm
12 cm
15 cm
17 cm
20 cm

Customised products on request

Description of item code

PTC-S/Jr-C-F1-0xx-L
(example: PTC-S-C-F5-035-150)

PTC	The guide wire is named after the Perkutan Transhepatic Cholangiograph procedure
S	Straight tip
Jr	J-tip radius J1,5 mm tip J3 mm tip J6 mm tip J15 mm tip
C	PTFE coated
Without C	Stainless steel
F1	Length of the distal flexible tip F5 - 5 cm flexible tip F7 - 7 cm flexible tip F10 - 10 cm flexible tip F12 - 12 cm flexible tip F15 - 15 cm flexible tip F17 - 17 cm flexible tip F20 - 20 cm flexible tip
0xx	Diameter of the guide wire 025: 0.025" (0.64 mm) 035: 0.035" (0.89 mm)
L	Length of the guide wire ■ 50 - 260 cm